

GNSS-804

Cutting-edge antenna technology with superior tracking performance



Innovative design with multiple patents

The VEXXIS GNSS-800 series antennas feature a patented multi-point feeding network and radiation pattern optimisation technology. In addition to having enhanced performance in multipath environments, the GNSS-804 antenna is able to maintain a low profile while achieving both high peak zenith gain and low gain roll-off from zenith to horizon without sacrificing tracking performance. This new technology significantly enhances the low elevation angle tracking capabilities, extending operation to the entire GNSS constellation. Furthermore, the antenna is able to achieve greater phase centre stability through our innovative element design. This directly translates into improved carrier phase measurement and a better RTK solution.

Tracking in challenging environments

The ability to track low elevation satellites while maintaining a high gain for higher elevation satellites makes the GNSS-804 an excellent choice for any applications where the sky is partially visible, such as operating close to tree lines, under foliage, or in urban canyons. The antenna is able to track any visible satellites from horizon to zenith, providing the maximum number of observations for an enhanced positioning solution.

Toughest precision antenna from Hexagon | NovAtel

GNSS-800 antennas are the toughest high-precision antennas NovAtel has designed to date, ensuring their survivability even in the harshest operating environments. The antennas feature ultra-durable watertight enclosures and have been proven to sustain intense vibration, earning the MIL-STD-810G rating.

Features

- Supports GPS, GLONASS, Galileo and BeiDou signal reception
- Multi-point antenna feed provides stable phase centre and enhanced multipath rejection
- Radiation pattern optimisation technology yields exceptional low elevation satellite tracking
- Provides exceptional tracking performance previously unachievable in a small form factor
- Hermetically-sealed enclosure to endure the toughest environment

Performance

Signal Received

GPS/QZSS	L1, L2
GLONASS	G1, G2
Galileo	E1, E5b
BeiDou	B1, B2

Pass Band (typical)

Upper passband	1588.0 ± 23.0 MHz
Lower passband	1225.5 ± 28.5 MHz

Out-of-Band Rejection

Band edges ± 50 MHz	40 dB minimum
Band edges ± 100 MHz	60 dB minimum

LNA Gain (typical)

29 dB

Gain at Zenith (90°)

L1/B1/E1/G1	+5.0 dBic minimum
L2/B2/E5b/G2	+5.0 dBic minimum

Gain Roll-Off (from Zenith to Horizon)

L1/B1/E1/G1	10 dB
L2/B2/E5b/G2	12 dB

Phase Centre Stability

<2.0 mm

Noise Figure (typical)

<2.0 dB

VSWR

≤2.0 : 1

L1-L2 Differential Propagation Delay

5 ns (maximum)

Group Delay Ripple

<15 ns

Nominal Impedance

50 Ω

Physical and Electrical

Dimensions

176 mm D × 55 mm H

Weight

507 g

Connector

TNC female

Mounting

5/8" thread mount

Power

Input voltage	+3.8 to +18.0 VDC
Current	55 mA (typical)

Environmental

Temperature

Operating	-40°C to +85°C
Storage	-55°C to +85°C

Humidity

95% non-condensing

Salt Fog

MIL-STD-810G (CH1), 509.6

Dust/Water Resistance

IP69K

Vibration (operating)

Random	MIL-STD-810G (CH1), 514.7 (7.7 g) Annex E, Procedure 1, Category 24
--------	--

Shock

MIL-STD-810G (CH1), 516.7 (40 g),
Procedure 1

Bump

IEC 60068-2-27 Ea (25 g)

Compliance

FCC, ISSED, CE

Contact Hexagon | NovAtel

sales.nov.ap@hexagon.com 1-800-NOVATEL (U.S. and Canada) or 403-295-4900 | China: 0086-21-68882300 | Europe: 44-1993-848-736 | SE Asia and Australia: 61-400-883-601.
For the most recent details of this product: novatel.com

This document and the information contained herein are provided AS IS and without any representation or warranty of any kind. All warranties, express or implied, are hereby disclaimed, including but not limited to any warranties of merchantability, non-infringement, and fitness for a particular purpose. Nothing herein constitutes a binding obligation. The information contained herein is subject to change without notice.

NovAtel and VEXXIS are trademarks of Hexagon AB and/or its subsidiaries and affiliates, and/or their licensors. All other trademarks are properties of their respective owners.

© Copyright 2016 – 2023 Hexagon AB and/or its subsidiaries and affiliates. All rights reserved. A list of entities within the Hexagon Autonomy & Positioning division is available at <https://hexagon.com/company/divisions/autonomy-and-positioning>.